
CS 290B

Scalable Internet Services


Andrew Mutz October 21, 2014



Today's Agenda

Motivation
Client-side Caching
Server-side Caching
For Next Time





We want our important application data persisted safely in our data center.

And it needs to be regularly read and updated by geographically distributed clients.

And it needs to be fast.

Performance Matters!

Delay	User Reaction
0 - 100 ms	Instant
100 - 300 ms	Slight perceptible delay
300 - 1000 ms	Task focus, perceptible delay
1 second+	Mental context switch
10 seconds+	I'll come back later

TA BARBA


Source: Ilya Grigorik (igvita.com)

But there are challenges:

Route	Distance	Time, light in vacuum	Time, light in fiber		
NYC to SF	4,148 km	14 ms	21 ms		
NYC to London	5,585 km	19 ms	28 ms		
NYC to Sydney	15,993 km	53 ms	80 ms		
Equator	40,075 km	133 ms	200 ms		

Source: High Performance Browser Networking, Ilya Grigorik

A page is more than a single request:




The fastest request is the one that never happens!

Cache: a component that transparently stores data so that future requests for that data can be served faster.

Where to introduce caching?

- Inside the browser
- In front of the server (CDNs, etc.)
- Inside the application server
- Inside the database (query cache)





How does the browser cache data? How does it know when it can safely present previously seen data as current?

The building blocks are all HTTP headers:

- etag
- cache-control
 - o max-age
 - no-cache
 - o no-store
 - public | private
- if-modified-since
- if-none-match



etag: "5bf444d26f9f1c74"

When accompanying a response, the browser will keep this "entity tag" along with saved copies of the resource.

When requesting the same resource in the future, this tag can be presented to indicate the version it had previously seen.

This isn't necessarily a digest of the resource that was served up, but can be thought of as such.

cache-control: no-cache

When accompanying a response, the browser (or intermediate proxy) is instructed to revalidate before reusing it.

Without this, the browser can use recently seen versions safely.



cache-control: max-age=120

When accompanying a response, the browser (or intermediate proxy) should consider this copy fresh until the specified number of seconds has passed.

The more modern version of the expires and date headers.



cache-control: no-store

When accompanying a response, the browser (or intermediate proxy) is instructed to not reuse this data under any circumstances.

This can also used for sensitive information.



cache-control: private

When accompanying a response, the browser (or intermediate proxy) is instructed that the data is specific to the requesting user.

Intermediate proxies should discard such data, but a single user browser can reuse it.

The opposite of this is cache-control: public

if-modified-since: Sun, 19 Oct 2014 19:43:31

When accompanying a request, this indicates that the client already has a copy that was fresh as of the specified date.

If the server's copy is newer than the specified date, it will be served to the client.

If the server's copy hasn't changed since the specified date, the server will return 304 (not modified).



if-none-match: "5bf444d26f9f1c74"

When accompanying a request, this indicates that the client has a cached copy with the associated tag. Multiple etags can be provided.

If the server's current version has one of the etags listed, the server will return 304 (not modified) with the etag of the current resource included.

If the server's version has a non-matching etag, then the result will be returned as normal.

Let's pull this together and apply what we've seen.

Let's say we are serving up some javascript that won't change over the next day, but does have some user-specific code in it.

What headers should the response include?

We want it reusable, but private:

Cache-control: private, max-age=86400



Let's say we are serving up an image that may be changing in the future, and we never want a stale version shown. The image is not specific to the requestor.

What headers should the response include?

We want it reusable with revalidation and public:

Cache-control: public, no-cache

ETag: "4d7a6ca05b5df656"

Clients will request the resource with:

if-none-match: "4d7a6ca05b5df656"



Let's say we are serving up an image with the user's social security and credit card numbers.

What headers should the response include?



We want it reusable, but private:

Cache-control: private, no-store



Today's Agenda


Motivation


Client-side Caching

Server-side Caching

For Next Time







Source: http://www.eecs.berkeley.edu/~rcs/research/interactive_latency.html

Category	Segment	% Time	Avg calls (per txn)	Avg time (ms)
Database	SQL - SELECT	15.9	18.7	65.3
View	occupancies/_sidebar_show.html.erb Partial	11.8	0.989	48.5
Controller	OccupanciesController#show	9.4	1.0	38.8
View	occupancies/_occupancy_financials_show.html.erb Partial	5.4	0.989	22
View	occupancies/_occupancy_status_show.html.erb Partial	4.3	0.989	17.5
View	occupancies/show.html.erb Template	3.8	0.989	15.5
View	occupancies/_occupancy_monthly_charges_show.html.erb Partial	2.8	0.989	11.6
View	notes/_note_show.html.erb Partial	2.3	1.29	9.41

From this data we can see that the network inside our datacenter is fast.

- Roundtrip inside the datacenter is about ~500ns
- Main memory access is ~100ns.

Reads from SSDs are faster, disk is slower

- 0.016ms to 0.2ms for SSD reads
- 4ms to 6ms for magnetic disk reads

Ruby/Rails is slow.

 Some partials are taking tens of milliseconds to render.



Basic math reveals opportunities for caching:

- If an entire page can be reused, storing it on disk and retrieving it when needed can bring big wins
 - o 5ms* vs. hundreds of milliseconds
- If only part of a page can be reused, it still may make sense to cache it on disk
 - o 5ms* vs. tens of milliseconds

- Instead of saving on disk, traversing the network and storing in memory can be faster*.
 - What are other advantages to non-local caching?



Caching has changed significantly in Rails 4.

Rails previously had mechanisms for caching entire pages and actions. As of Rails 4, these have been moved to a separate library called actionpack-page_caching.

Rails now emphasizes three types of caching:

- HTTP caching
- Fragment caching
- Low level caching



By default, caching is disabled in development and test, and enabled in production

If you want to use it in development mode, add this to your environment:
 config.action_controller.perform_caching = true

Rails can be configured to store cached data in a few different places:

- In memory
- Local file system
- Remote in-memory store



ActiveSupport::Cache::MemoryStore

- Cached data is stored in memory, in the same address space as the ruby process and is retained between requests.
- Defaults to 32 megs, but is configurable.
- Strengths?
- Weaknesses?



ActiveSupport::Cache::MemoryStore

- Cached data is stored in memory, in the same address space as the ruby process and is retained between requests.
- Defaults to 32 megs, but is configurable.
- Strengths:
 - Local memory is fast
- Weaknesses:
 - We are likely running many Rails processes on a single machine, and these processes can't use each others memory cache.



ActiveSupport::Cache::FileStore

- Cached data is stored on the local file system.
- Can configure the location of the storage in Rails environment:
 - o config.cache_store = :file_store, "/path/to/cache/directory"
- Strengths?
- Weaknesses?



ActiveSupport::Cache::FileStore

- Cached data is stored on the local file system.
- Can configure the location of the storage in Rails environment:
 - o config.cache_store = :file_store, "/path/to/cache/directory"
- Strengths
 - A pool of processes on the same machine can now share the same cache.
- Weaknesses
 - Disk isn't all that fast
 - If our production deployment has many machines, they can't share caches.



ActiveSupport::Cache::MemcacheStore

- Cached data is stored in memory on another machine.
- Can configure the location of the server in Rails environment:
 - o config.cache_store = :mem_cache_store, "cache-1.example.com"
- Strengths
 - A pool of processes across machines can now share the same cache.
 - As we've seen, intra-datacenter network round trip and memory access can give us ~1ms responses.
- Weaknesses
 - System complexity

Rails Caching - HTTP Caching

HTTP Caching: Rails makes this easy

- By default, Rails sets the etag to an MD5 digest of the content body.
 - If subsequent requests generate the same body, a 304 is sent instead of the body.
 - This is network efficient and easy, but what's still inefficient?



Rails Caching - HTTP Caching

We're still generating the response each time.

Solution:



Whole-page caching is great when possible, but for dynamic web applications, it frequently isn't.

Fragment caching caches a portion of a rendered view for reuse on future requests.

For example, we may have a page listing recent orders (dynamic) alongside a list of products (less dynamic)

```
<% Order.find recent.each do |o| %>
  <%= o.buyer.name %> bought <%= o.product.name %>
<% end %>
<% cache 'all_available_products' do %>
 All available products:
  <% Product.all.each do |p| %>
   <%= link to p.name, product url(p) %>
  <% end %>
<% end %>
```



When the products **do** change, the fragment must be expired using

expire_fragment('all_available_products')

Manually managing cache expiration can be tricky and lead to bugs.

Can you think of a better way?

```
module ProductsHelper
 def cache_key_for_products
    count = Product.count
   max_updated_at = Product.maximum(:updated_at).utc.to_s, :number)
    "products/all-#{count}-#{max updated at}"
 end
end
<% cache(cache key for products) do %>
 All available products:
    <% Product.all.each do |p| %>
    <%= link to p.name, product url(p) %>
  <% end %>
<% end %>
```



Another option is to use the model itself as the cache key:

Which will generate a cache key that includes the updated_at timestamp (something like "products/23-20130109142513").

We can also nest our fragment caching, for a style referred to as "Russian Doll Caching":

```
<% cache(cache_key_for_products) do %>
  All available products:
  <% Product.all.each do |p| %>
       <% cache(p) do %>
       <%= link_to p.name, product_url(p) %>
       <% end %>
  <% end %>
```



Rails Caching - Manual Caching

Manual Caching is also supported, for fine-grained control:

```
#product.rb

class Product
  def competing_price
    Rails.cache.fetch("/product/#{id}-#{updated_at}/comp_price",
        expires_in => 12.hours) do
    Competitor::API.find_price(id)
    end
end
end
```



For Next Time...

Be in a group for tomorrow's lab. We will be kicking off projects.

Citrix data center tour Nov 6!

By tomorrow at noon, put on Piazza:

- Team name
- For each team member
 - Name, Github account name, Email

